Tread Grit® HD





DESCRIPTION: Tread Grit HD (Heavy Duty) is applied to Form-A-Tread to increase traction on wet, oily, exterior and high traffic surfaces. Tread Grit HD is an extremely hard compound and has excellent adhesion to Form-A-Tread when applied immediately after spreading. Tread Grit HD is translucent so it does not mask the color of the underlying Form-A-Tread.

Features/Benefits

- Improved Traction
- Increased Durability
- Does Not Mask Color
- Improves UV Resistance
- Excellent Adhesion to Form-A-Tread

DIRECTIONS: Shake Tread Grit HD on Form-A-Tread immediately after spreading.

Physical Properties

*Coverage (Kits per Container Size)

Physical Properties	Value
Appearance	Angular/Translucent
Specific Gravity	3.94g/cc
Bulk Density	1.80g/cc
Hardness	MOH 9.0

Containter Size	400ml Kits
226g Jar	1
800g Jar	3.5
12 lb Pail	24

^{*}Coverage is based on application to the point of refusal. Coverage increases with lower application rates.

ATSM F609 - Test Results

Slip Resistance of Form-A-Tread with Tread Grit HD Applied*

Dry	Static Load (lbf)	Static Coefficient of Friction	Slip Index
Average	3.9	0.65	6.5
Wet	Static Load (lbf)	Static Coefficient of Friction	Slip Index
Average	4.3	0.71	7.1

^{*}Note: Tread Grit HD was applied to the point of refusal.